



TECHNOCOAT 4040

RI

Description:

A specially formulated cementitious leveling and correction mortar that provides excellent adhesion and durability and can be used in multi-purpose applications.
concrete walls, and ceilings.

Area of Use:

Used to provide a smooth surface prior to interior and exterior painting, tiling, and building insulation. It is suitable for use on cement plaster, concrete, and smooth concrete surfaces. It is also suitable for use on rough plaster, cellular concrete, brick, and light concrete walls and ceilings.

Properties:

High adhesion strength. Creates a smooth and durable surface. Resistant to the freeze-thaw cycle. Applies in thicknesses ranging from 3 to 7 mm.

Easy to apply

Application information:

Application temperature range: ($^{\circ}5+C$) - ($^{\circ}35+C$). Shelf life: approximately 4 hours. Mixing ratio: 6-5.2 liters of water/20 kg of powder. Thickness: 7-3 mm. Average consumption: 1.5 kg/m²





How to Use:

Pour Empire Technocoat 4040 into the recommended amount of water and mix slowly until a homogeneous mixture is obtained. Mix using a low-speed mixer. Do not add any additives not specified in the instructions for use. Allow the prepared mortar to set for 10-5 minutes. Mix again for 2-1 minutes before use. Apply Empire Technocoat 4040 using a steel trowel, applying a layer no thicker than 7 mm.

Storage:

Store the product dry at a temperature between 5 and °35C in a moisture-free environment. Avoid exposure to direct sunlight. Protect the product from water, frost, and adverse weather conditions. Shelf life is a maximum of 12 months, provided the above conditions are met.

