



# TechnoFuga filler 705

## DESCRIPTION

Empire Techno FUGA FILLER is a high-quality acrylic resin-based mortar with selected mineral particles and special additives, which provide excellent bonding with FUGA, XPS, and EPS board.

Empire TechnoFUGA FILLER can be used manually or with a jamb coating machine application to provide a smooth hard finish.

## USES

Indoors and outdoors.  
Horizontal or vertical surfaces.

For the coating and repair of thermal insulating materials such as EPS-XPS.

## ADVANTAGES

Ready to use.

Excellent water resistance.

Excellent alkali resistance.

It forms a smooth surface in the cast due to its fine particle structure.

It provides an aesthetic appearance to the buildings.

It does not cause slipping on the surface due to its high adherence property.

It may be applied on the surface manually or pasting machine.

Not affected by UV, extremely high or low temperatures, or adverse weather conditions such as rain, snow, or humidity, it does not swell, crack or discolor.

Odour-free and does not harm human and environmental health.





# PRODUCT & TECHNICAL DATA

Consistency Putty  
Colour Yellowish white  
Mix Density 1.58 g/cm<sup>3</sup>  
Ph 9.5-8.5  
Wet Layer Thickness 4 mm  
Drying Time (°23+C) 24 hours (°23+C) (Drying time varies depending on temperature and humidity)  
Through Time (°23+C) 4 hours (°23+C)  
Application: Ambient Air  
Temperature (°5+C) - (°50+C)

## Application Method

### Surface Preparation

Surfaces must be clean, smooth, durable, and free of non-adhesive materials and deposits such as dust, oil, dirt, corrosion, mold oil, and detergents. Highly porous surfaces must be dried at saturation surface temperature (SSD).